



F15EV

Technical Specifications

Frequency Range (+/-3 dB)	65 Hz - 20 kHz
Nominal Directivity (-6 dB) H x V	60° x 40°
Maximum Peak SPL (LF / MF / HF)	139 / 141 / 136 dB
Components LF	1 x 15in. Ferrite cone driver
Components MF	2 x 6.5in. Neodymium cone driver
Components HF	1 x 2in. exit Neodymium compression driver
Nominal Impedance LF	8 Ω
Nominal Impedance MF	8 Ω
Nominal Impedance HF	8 Ω
Power Handling (AES / Peak) LF	1.500 / 6.000 W
Power Handling (AES / Peak) MF	360 / 1.440 W
Power Handling (AES / Peak) HF	110 / 440 W
Rigging	VH e-motion rigging™ system (optional touring version)
Connections	2 x SpeakON™ NL8 - 1 x NL4 Sub/Bass out
Enclosure Construction	18 / 24 mm Birch-ply
Finish	Black Polyurea PCP (Polyurea Cabinet Protection) finish
Protection Grille	Powder coated 2mm Rigid Metal Grille
	Acoustically transparent Foam for discrete appearance
Height Front (mm / in.)	918 / 36.14
Height Back (mm / in.)	918 / 36.14
Width Front (mm / in.)	661 / 26.02
Width Back (mm / in.)	340 / 13.38
Depth (mm / in.)	639 / 25.15
Weight (kg / lbs)	67 / 147.70
Supported Processing	Armonia Pro Audio Suite