



## VH Layer EMD

### Technical Specifications

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Frequency Range (+/-3 dB)         | 350 Hz - 1.65 kHz                |
| Nominal Directivity (-6 dB) H x V | 90° x 10°                        |
| Maximum Peak SPL (MF)             | 141 dB                           |
| Components MF                     | 2 x 6.5in. Neodymium cone driver |
| Nominal Impedance MF              | 8                                |
| Power Handling (AES / Peak) MF    | 360 / 1.440 W                    |
| Rigging                           | LayerEMD™ rigging system         |
| Connections                       | 1 x SpeakON™ NL4                 |
| Enclosure Construction            | ABS                              |
| Finish                            | Acrylic two-component finish     |
| Protection Grille                 | N.A.                             |
| Height Front (mm / in.)           | 450 / 17.71                      |
| Height Back (mm / in.)            | 450 / 17.71                      |
| Width Front (mm / in.)            | 472 / 18.58                      |
| Width Back (mm / in.)             | 346 / 13.62                      |
| Depth (mm / in.)                  | 371 / 14.61                      |
| Weight (kg / lbs)                 | 8 / 17.63                        |
| Supported Processing              | Armonia Pro Audio Suite          |